



216 Tuckerton Rd
Medford NJ 08053
856-983-5676

DEFINITIVE TECHNOLOGY

*Prices subject to change, updated 8/11/11

BIPOLAR SUPER TOWER

(All Towers Available in Gloss Black)

<u>Model</u>	<u>Description</u>	<u>Price</u>
BP700SC	Response 11Hz – 30KHz Impedance 8 ohms, rated 20-1,000 watts 14" 1,800 watt super cube built in sub 4 6-1/2" mid range drivers 2 1" aluminum dome tweeters	2,199.99/ea. 4,399.99/pr.
BP8080ST	SuperTower floor-standing loudspeaker Bipolar loudspeaker with built-in powered subwoofer Driver complement: 3 each 5 1/4" BDSS midrange drivers, 2 each 1" aluminum dome tweeters, 1 each 12" active subwoofer driver pressure coupled to 2 each 12 1/2" low-bass radiators Frequency response: 18Hz – 30kHz Nominal impedance: 8 ohms Recommended amplifier power: 20-400 watts A/V receiver crossover setting: large, full bandwidth Internal amplifier power: 455 watts Auto on/off: signal sensing Inputs: 1 pair of 5-way binding posts, 1 LFE input (optional) Accessories: stabilizer feet, carpet spikes, hard floor glides Product weight: 66 lbs. H48-1/4 x W7 x D16-5/16 – cabinet only H48-1/4 x W12-1/8 x D16-5/16 – with stabilizer feet	1,349.99/ea 2,699.98/pr

BP8060ST	<p>BP8060 SuperTower floor-standing loudspeaker Bipolar loudspeaker with built-in powered subwoofer Driver complement: 3 each 4 ½" BDSS midrange drivers, 2 each 1" aluminum dome tweeters, 1 each 10" active subwoofer driver pressure coupled to 2 each 10" low-bass radiators Frequency response: 20Hz – 30kHz Sensitivity: 92dB Nominal impedance: 8 ohms A/V receiver crossover setting: large, full bandwidth Internal amplifier power: 300 watts Auto on/off: signal sensing Inputs: 1 pair of 5-way binding posts, one LFE input (optional) Accessories: stabilizer feet, carpet spikes, hard floor glides Product weight: 54 lbs. H44-3/16 x W5-15/16 x D13-7/16 – cabinet only H44-3/16 x W11-1/16 x D13-7/16 – with stabilizer feet</p>	<p>899.99/ea 1,799.98/pr</p>
BP8040ST	<p>SuperTower floor-standing loudspeaker Bipolar loudspeaker with built-in powered subwoofer Driver complement: 3 each 3 ½" BDSS midrange drivers, 2 each 1" aluminum dome tweeters, 1 each 8" active subwoofer driver pressure coupled to 2 each 8" low-bass radiators Frequency response: 25Hz – 30kHz Nominal impedance: 8 ohms Recommended amplifier power: 20 – 300 watts per channel A/V receiver crossover setting: large, full bandwidth Internal amplifier power: 300 watts Auto on/off: signal sensing Inputs: 1 pair of 5-way binding posts, one LFE input (optional) Accessories: stabilizer feet, carpet spikes, hard floor glides Product weight: 40 lbs. H39 x W5-5/8 x D11-5/8 – cabinet only H39 x W10-3/4 x D11-5/8 – with stabilizer feet</p>	<p>719.99/ea 1,439.98/pr</p>
BP8020ST	<p>BP8020 SuperTower floor-stand loudspeaker Bipolar loudspeaker with built-in powered subwoofer Driver complement: 3 each 3 ½" midrange drivers, 1 each 1" aluminum dome tweeter, 1 each 8" active subwoofer driver Frequency response: 30Hz – 30kHz Nominal impedance: 8 ohms Recommended amplifier power: 20- - 250 WPC Internal amplifier power: 150 watts Auto on/off: signal sensing Inputs: 1 pair of 5-way binding posts, one LFE input (optional) Accessories: stabilizer feet, carpet spikes, hard floor glides Product weight: 34 lbs. H35-7/8 x W5-5/8 x D11-5/8 H91cm x 14.2cm – cabinet only H35-7/8 x W10-3/4 x D11-5/8 H91cm x W27.2cm x D29.4cm – w/stabilizer feet</p>	<p>539.99/ea 1,079.98/pr</p>

BP10B	Response 20Hz – 30KHz Rated 20-200 watts Impedance 8 ohms Two 25mm aluminum dome tweeters Two 17cm cast magnesium basket bass/midrange	499.99/ea. 999.99/pr.
BP8B	Response 22Hz – 30KHz Rated 20-200 watts Impedance 8 ohms Two 25mm aluminum dome tweeters Two 14cm magnesium basket bass/midrange	449.99/ea. 899.99/pr.
BP6B	Response 25Hz – 30KHz Rated 20-175 watts Impedance 8 ohms Two 25mm aluminum dome tweeters Two 14cm bass/midrange	349.99/ea. 699.99/pr.

STUDIO MONITORS BOOKSHELF SPEAKERS

Studio Montior 450 SKU# SM450	1 – 1” dome tweeter 1 – 6-1/2” bass/mid driver 1 – 10” bass radiator Gloss black H13 x W8-3/4 x D11-1/2	549.99
Studio Monitor 350 SKU# SM350	1 – 1” dome tweeter 1 – 5-1/4” bass/mid driver 1 – 8” bass radiator Gloss black H10-3/4 x W7 x D9-3/4	449.99

BIPOLAR SURROUND SPEAKERS

SR8080BP	Bipolar surround loudspeaker Driver complement: 2 each 4 ½" drivers, 2 each 1" aluminum dome tweeters Frequency response: 40Hz – 30kHz Nominal impedance: 8 ohms Recommended amplifier power: 20 – 200 WPC A/V receiver crossover setting: Inputs: 1 pair of 5-way binding poasts Product weight: 13 lbs. H15-5/8 x W9 x D6-1/16	319.99/ea 639.98/pr
SR8040BP	Bipolar surround loudspeaker Driver complement: 2 each 3 ½" drivers, 2 each 1" aluminum dome tweeters Frequency response: 50Hz – 30kHz Nominal impedance: 8 ohms Recommended amplifier power: 20 – 150 WPC Inputs: 1 pair of 5-way binding posts Product weight: 8 lbs. H9-1/2 x W7-13/16 x D5-3/8 H24cm x W19.8cm x D13.5cm	229.99/ea 459.98/pr

CENTER CHANNEL SPEAKERS

(All Center Channels Available in Piano Gloss Black)

CS8080ST	Matches BP8080ST Center channel loudspeaker w/built-in powered subwoofer Driver complement: 2 each 5 ¼" (13cm) BDSS midrange drivers, 1 each 1" (25mm) aluminum dome tweeter, 1 each 5"x10" active subwoofer driver pressure coupled to 2 each 5"x10" low-bass radi Frequency response: 20Hz – 30kHz Nominal impedance: 8 ohms Recommended amplifier power: 20 – 300 watts A/V receiver crossover setting: large, full range Internal amplifier power: 300 watts Auto on/off: signal sensing Inputs: 1 pair of 5-way binding posts, one LFE input (optional) Product weight: 33 lbs. H6-3/4 x W23-1/2 x D14	899.99/ea
----------	--	-----------

CS8060ST	<p>Matches BP8060ST</p> <p>Center channel loudspeaker with built-in powered subwoofer Driver complement: 2 each 4 ½" BDSS bass/midrange drivers, 1 each 8" active woofer, 1 each 1" aluminum dome tweeter Frequency response: 30Hz – 30kHz Nominal impedance: 8 ohms Recommended amplifier power: 20-250 watts A/V receiver crossover setting: large, full range Internal amplifier power: 150 watts Inputs: 1 pair 5-way binding posts, low level woofer in (optional) Product weight: 26 lbs. H5-3/4 x W21-1/8 x D12</p>	629.99/ea
CS8040ST	<p>Matches BP8040ST</p> <p>Center channel loudspeaker with built-in powered subwoofer Driver complement: 2 each 4 ½" BDSS bass/midrange drivers coupled to 1 each 5"x10"bass radiator, 1 each 1" aluminum dome tweeter Frequency response: 40Hz – 30kHz Nominal impedance: 8 ohms Recommended amplifier power: 20-200 watts A/V receiver crossover setting: small, 80Hz Inputs: 1 pair 5-way binding posts Product weight: 20 lbs./9 kg. H5-3/4 x W21-1/8 x D12</p>	449.99/ea
Pro Center 2000	<p>One 1" dome tweeter, Two 5-1/4" BDSS bass/mid driver Two 5-1/4" sub radiators H6-1/2 x W17 x D6-1/2</p>	299.99
Pro Center 1000	<p>One 1" dome tweeter, Two 4-1/2" BDSS bass/mid drivers, Two 5-1/2" sub radiators H5 x W14-1/4 x D5</p>	

OUTDOOR SPEAKERS

<p>AW6500 SKU# AW6500B (Black) SKU# AW6500W (White)</p>	<p>All-weather in/out speakers 1 – 1" dome tweeter 1 - 6-1/2" BDSS bass/mid 1 – 5-1/2" x 10" bass radiator Bracket included H14-1/2 x W9 x D9-1/4</p>	<p>199.99 ea. 399.98 pr.</p>
<p>AW5500 SKU# AW5500B (Black) SKU# AW5500W (White)</p>	<p>All-weather in/out speaker 1 – 1" dome tweeter 1 – 5-1/4" BDSS mid/bass 1 – 5" x 8" bass radiator Bracket included Black/white H12-3/4 x W7-3/4 x D8-1/8</p>	<p>159.99 ea. 319.99 pr.</p>

MYTHOS ULTRA THIN

Mythos XTR60	Ultra-slim, ultra-high performance on-wall or on-shelf loudspeaker Driver complement: 4 each 3-1/2" XTDD anodized aluminum dome mid/bass drivers pressure coupled to 4 each 3-1/2" dome low-bass radiators, 1 each 1" pure aluminum dome tweeter Frequency response: (overall on wall) 70Hz – 30kHz Nominal impedance: 8 ohms nominal Recommended amplifier power: 30 – 200 watts per channel Enclosure: extruded aluminum, sealed Supplied accessories: smoked glass base table stand, wall mount bracket, adjustable support foot for horizontal shelf placement, magnetic logos Available finishes: high gloss black Mounted on wall without bracket - H32 x W6 x D1-1/2 x D38mm Mounted on wall with bracket - H32 x W6 x D1-9/16 On table stand - 35" Table stand base dimensions - W8-11/16 x D4-3/4	809.99/each 1,619.98/pr
Mythos XTR50	Ultra-slim, ultra-high performance on-wall or on-shelf loudspeaker Driver complement: 2 each 3 1/2" XTDD anodized aluminum dome mid/bass drivers pressure coupled to 4 each 3 1/2" dome low-bass radiators, 1 each 1" pure aluminum dome tweeter Frequency response: (overall on wall) 92Hz – 30kHz Nominal impedance: 8 ohms nominal Recommended amplifier power: 20 – 100 watts per channel Enclosure: extruded aluminum Product weight (without table stand) 5.1 lbs. (2.3kg.) Supplied accessories: smoked glass base table stand, wall mount bracket, adjustable support foot for horizontal shelf placement, magnetic logos Available finishes: high gloss black Mounted on wall without bracket – H27 x W6 x D1-1/2 Mounted on wall with bracket – H27 x W6 x D1-9/16 On table stand – H30 Table stand base dimensions – W8-11/16 x D4-3/4	629.99/ea 1,259.98/pr
Mythos XTR40	Ultra-slim, ultra-high performance on-wall loudspeaker Driver complement: 2 each 3-1/2" XTDD anodized aluminum dome mid/bass drivers pressure coupled to 2 each 3-1/2" dome low-bass radiators, 1 each 1" pure aluminum dome tweeter Frequency response: (overall on wall) 100Hz – 30kHz Nominal impedance: 8 ohms nominal Recommended amplifier power: 20 – 100 watts per channel Enclosure: extruded aluminum, sealed Supplied accessories: wall mount bracket, adjustable support foot for horizontal shelf placement, magnetic logos Available finishes: high gloss black Mounted on wall without bracket – H23-1/4 x W6 x D1-1/2 Mounted on wall with bracket – H23-1/4 x W6 x D1-9/16	449.99/ea 899.98/pr

Mythos XTR20BP	Slim, bipolar surround speaker Driver complement: 2 each 3-1/2" XTDD anodized aluminum dome mid/bass drivers in a bipolar array, 1 each 1" pure aluminum dome tweeter Frequency response: (overall on wall) 100Hz – 30kHz Nominal impedance: 8 ohms nominal Recommended amplifier power: 20 – 100 watts per channel Enclosure: extruded aluminum, sealed Supplied accessories: wall mount bracket, adjustable support foot for horizontal shelf placement, magnetic logos Available finishes: high gloss black Mounted on wall without bracket – H11-7/8 x W6 x D2-1/2 Mounted on wall with bracket – H11-7/8 x W6 x D2-9/16	249.99/ea 499.98/pr
----------------	--	------------------------

MYTHOS ON-WALL BOOKSHELF

Mythos Ten	On-wall main and center L/C/R loudspeaker 1 – 1" dome tweeter 2 – 5 1/4" mid/bass drivers 2 – 5" x 8" sub radiators H6 x W34-1/2 x D4-1/2	799.99/ea.
Mythos Nine	On-wall, on shelf and L/C/R loudspeaker 1 – 1" dome tweeter 2 – 4 1/2" BDSS bass 2 – 4 1/2" x 8" sub radiators	699.99/ea.
Mythos Eight	On-wall main and center L/C/R loudspeaker 1 – 1" dome tweeter 2 – 5 1/4" mid/bass drivers 2 – 5 1/4" sub radiators H6 x W28-1/2 x D4-1/2	649.99/ea.
Mythos Three	Table top & on wall center loudspeaker To match Mythos Two 1 – 1" dome tweeter 2 – 4 1/2" mid/bass drivers 2 – 4 1/2" sub radiators H5-1/2 x W25-1/2 x D4-1/4	499.99/ea.
Mythos Two	Table top & on wall loudspeaker 1 – 1" dome tweeter 2 – 4 1/2" mid/bass drivers 2 – 4 1/2" sub radiators H25 x X4-1/4 x D5-1/2 H1-1/2 x W8 x D6-1/2 – pedestal	499.99/ea. 999.98/pr.

Mythos Seven	Table top & on wall center loudspeaker To match Mythos Six or Gem 1 – 1” dome tweeter 2 – 3 ½” mid/bass drivers 2 – 3 ½” sub radiators H4 x W19-1/2 x D4	349.99/ea.
Mythos Six	Table top and on-wall loudspeaker 1 – 1” dome tweeter 2 – 3 ½” mid/bass drivers 2 – 3 ½” sub radiators H19-1/2 x W4 x D4 H1-1/2 x W6-1/2 x D5-1/2 – pedestal	349.99/ea. 699.99/pr.
Mythos GemXL	1 – 1” dome tweeter 2 – 4 ½” mid/bass drivers H12-1/2 x W5-1/2 x D4-1/2	299.99/ea. 599.99/pr.
Mythos Gem	1- 1” dome tweeter 2 – 3 ½” mid/bass drivers H10-1/4 x W4 x D4-1/4	499.99/pr.

MYTHOS TOWER SPEAKERS

(All Mythos Series are Polished Extruded Aircraft-Grade Black Aluminum)

Mythos Super Tower With Built-In Supercube

Mythos ST	1 – 1” dome tweeter 2 – 5 ¼” BDSS bass/mid drivers 1 – 6” x 10” long Throw racetrack subwoofer 1 – 6” x 10” sub radiators 300 watt Supercube amp H53 x W6-3/4 x D9-1/2 – pedestal W11-1/2 x D16 – pedestal	1,599.99/ea. 3,199.98/pr.
Mythos STS	1 – 1” dome tweeter 2 – 4 ½” BDSS bass/mid drivers 1 – 5” x 10” long throw racetrack subwoofer 2 – 5” x 10” sub radiators 300 watt Supercube amp H47-1/2 x W5-1/2 x D8-1/2 W10-1/2 x D14 – pedestal	1,299.99/ea. 2,599.99/pr.

Passive Floorstanding Models

Mythos One	1 – 1” dome tweeter 2 – 5 ¼” bass/mid drivers 2 – 5 ¼” bass drivers 2 – 5 ¼” sub radiators H48-1/2 x W6 x D6 W10 x D9-3/4 – pedestal	849.99/ea. 1,699.99/pr.
Mythos Four	1 – 1” dome tweeter 2 – 4 ½” bass/mid drivers 2 – 4 ½” bass drivers 2 – 4 ½” sub radiators H43-1/2 x W5-1/8 x D5-1/4 W8-3/4 x D8-1/2 – pedestal	699.99/ea. 1,399.99/pr.
Mythos Five	1 – 1” dome tweeter 2 – 3 ½” bass/mid drivers 2 – 3 ½” bass drivers 2 – 3 ½” sub radiators H40-3/4 x W4 x D4 W8-1/4 x D8 – pedestal	499.99/ea. 999.99/pr.

MYTHOS SOLO SURROUND ARRAYS

Mythos SSA50	3 – 4 ½” BDSS coincident array with 1” dome tweeters 2 – 4 ½” BDSS full range drivers 4 – 3 ¼” full range surround drivers H5-1/2 x W46-1/4 x D4-1/4	899.99
XTRSSA5	Mythos XTR-SSA5 ultra-thin single speaker surround bar Five discrete channels from one superb speaker The perfect surround audio solution when you are unable to use rear channel speakers Ultra slim design, only 1-5/8" deep, perfect for ultra thin LED TVs Wall mount bracket and table stand included The dynamic punch, wide frequency range and broad dispersion of full size speakers Aircraft grade extruded Aluminum enclosure Dimensions: :45" L x 1-5/8" D x 5-1/4" H Driver Complement: :10 each 3-1/2" XTDD dome mid/bass drivers 3 each 1"Pure Aluminum Dome Tweeters Frequency Response: :60Hz - 30kHz Sensitivity: :90dB Nominal Impedance: :8 Ohms	999.99/ea.

XTRSSA3	<p>Mythos XTR-SSA5 ultra-thin single speaker surround bar 799.99/ea.</p> <p>SAME FEATURES AS XTRSSA3 WITH:</p> <p>Three channels from one superb speaker</p> <p>Dimensions :43" L x 1-5/8" D x 5-1/4" H</p> <p>Driver Complement: :6 each 3-1/2" XTDD dome mid/bass drivers; 3 each 1" Pure Aluminum Dome tweeters</p> <p>Frequency Response :60Hz - 30kHz</p> <p>Sensitivity :90dB</p> <p>Nominal Impedance :8 Ohms</p>	
---------	--	--

Mythos SSA42	<p>3 – 3 ½” BDSS coincident array with 1” dome tweeters</p> <p>2 – 4 ¼” BDSS full range drivers</p> <p>4 – 3” full range surround drivers</p> <p>H4-1/8 x W40 x D4-1/4</p>	699.99
--------------	--	--------

PRO CINEMA SYSTEMS

Pro Cinema 1000	<p>4 – PM1000</p> <p>1 – PC1000</p> <p>1 – PS1000</p>	<p>Save 10%</p> <p>When Purchased in Package</p>	1,349.99
-----------------	---	--	----------

Pro Cinema 800	<p>4 – PM800</p> <p>1 – PC1000</p> <p>1 – PS800</p>	<p>Save 10%</p> <p>When Purchased in Package</p>	999.99
----------------	---	--	--------

Pro Cinema 600	<p>4 – PM600</p> <p>1 – PC600</p> <p>1 – PS600</p>	<p>Kit Only</p>	799.99
----------------	--	-----------------	--------

Pro Cinema 60	<p>4 – PM60</p> <p>1 – PC60</p> <p>1 – PS60</p>	<p>Kit Only</p>	699.99
---------------	---	-----------------	--------

Pro Monitor 1000 SKU# PM1000B (Black) SKU# PM1000W (White)	Compact main or surround speaker 1 – 1” dome tweeter 1 – 5 ¼” BDSS bass/midrange 1 – 5 ¼” sub radiator H10-7/8 x W6-1/4 x D6-1/2	199.99/ea.
Pro Monitor 800 SKU# PM800B (Black) SKU# PM800W (White)	Compact main or surround speaker 1 – 1” dome tweeter 1 – 4 ½” BDSS bass/midrange 1 – 4 ½” sub radiator H8-3/8 x W4-3/4 x D5	129.99/ea.
Pro Center 2000 SKU# PC2000	Compact center speaker 1 – 1” dome tweeter 2 – 5 ¼” BDSS bass/midrange 2 – 5 ¼” sub radiators H6-1/2 x W17 x D6-1/2	299.99
Pro Center 1000 SKU# PC1000B (Black) SKU# PC1000W (White)	Compact center speaker 1 – 1” dome tweeter Two 4 ½” BDSS bass/midrange Two 4 ½” Sub radiators H5 x W14-1/4 x D5	199.99
Pro Center 600 SKU# PC600	Compact center speaker 1 – 1” dome tweeter Two 3 ¼” BDSS bass/midrange Two 3 ¼” Sub radiators H4 x W10-1/2 x D4-1/4	Systems Only

IN-WALL SPEAKERS

UIW94/A	9" cast-basket round Pivoting 1" pure aluminum dome/silk surround neodymium magnet tweeter Dimensions: 10 3/4" diameter Cut-out size: 9-5/8" Rec. Ampl.: 10-300 watts Frequency response: 26Hz – 30KHz	499.99/pr.
UIW83/A	8" long-thros stamped basket woofer 1" pure aluminum dome tweeter Dimensions: 10" diameter Cut-out size: 9" Rec. Ampl.: 10-250 watts Frequency response: 27Hz – 30KHz	399.99/pr.
UIW64/A	Cast magnesium basket high definition 6 1/2" driver Pivoting pure aluminum dome tweeter Dimensions: 8 3/4" diameter Cut-out size: 7-5/8" Rec. Ampl.: 10-200 watts Frequency response: 28Hz – 30KHz	349.99/pr.
UIW63/A	A fixed 1" pure aluminum dome tweeter 6 1/2" bass/midrange driver Dimensions: 8 3/4" diameter Cut-out size: 7-5/8" Rec. Ampl.: 10-200 watts Frequency response: 30Hz – 30KHz	229.99/pr.
UIWBP/A	Two new 1" pure aluminum dome tweeters Bass/midrange drivers are our cast-basket 5 1/4" Dimensions: W7-1/8 x H12-1/2 Cut-out size: 6-1/8 x 7/16 Rec. Ampl.: 10-250 watts Frequency response: 28Hz – 30KHz	249.99/ea. 499.99/pr.
UIWBPZ/A	Two cast-magnesium basket 6 1/2" drivers Two new 1" pure aluminum dome tweeters Dimensions: W8-1/2 x H14-3/4 Cut-out size: 13-5/8 x 7-5/16 Rec. Ampl.: 10-300 watts Frequency response: 26Hz – 30KHz	749.99/pr.

ULTIMATE IN-WALL SPEAKERS

UIWBP/A	Response 28Hz – 30KHz Rated 10-250 watts, 8 ohms Two 5 ¼” bipolar drivers Built-in dome tweeters	249.99/ea. 499.99/pr.
UIW75	Response 26Hz – 30KHz Rated 10-300 watts, 8 ohms Two 6 ½” bass/midrange drivers One 1” aluminum dome tweeter	299.99/ea. 599.99/pr.
UIW65	Response 28Hz – 30KHz Rated 10-175 watt, 9 ohms One 6 ½” bass midrange One 1” aluminum dome tweeter	399.99/pr.
UIW55	Response 35Hz – 30KHz Rated 10-175 watts, 8 ohms One 5 ¼” bass/midrange One 1” aluminum dome tweeter	299.99/pr.
RP65	Deluxe EZ mount rough-in bracket for UIW65	29.99/pr.
RB55	Deluxe EZ mount rough-in bracket for UIW55	29.99/pr.
RB63/64	Deluxe EZ mount rough-in bracket for UIW63/64	29.99/pr.
RBBP	Deluxe EZ mount rough-in bracket for UIWBP	29.99/pr.

DISAPEARING IN-WALL SPEAKER SERIES

DI6.5LCR

Disappearing In-Wall series dual 6-1/2" in-wall loudspeaker for LCR applications

299.99/ea.

599.98/pr.

Extraordinary High-Performance Speakers that Virtually Disappear in Your Room!

Flangeless design & micro-perf grille minimize visibility
Simple to install — no spackle work required
Small enough to fit between studs in horizontal orientation
Latest generation BDSS drivers for audiophile-grade sound quality
Accurate response for ideal music and movie sound
Pivoting Pure Aluminum dome tweeters
Axially Aligned design ensures broad, balanced coverage area
Sure-grip magnetic grille fasteners
Adjustable high-definition crossover
Cast PolyStone™ baskets for rigidity without “ringing”
Grille Length :17-1/8"
Grille Width :8-5/16"
Cutout Length :16-3/16"
Cutout Width :7-5/16" (18.6cm)
Total Depth from flange to deepest part of product:3-5/8"
Mounting Depth In-Wall in 1/2" (12.7 mm) material:3-1/8"
Mid/Woofer :2@6-1/2"
Tweeter :1@1"
Product Weight :8.5 lbs
Frequency Response :26Hz - 30kHz
Sensitivity :90dB
Impedance :Nominal 4-8 Ohms
Recommended Amplifier Power :10 - 275 WPC

DI5.5LCR

Disappearing In-Wall series dual 5-1/4" in-wall loudspeaker for LCR applications

259.99/ea.

519.98/pr.

SAME FEATURES AS DI6.5 LCR WITH:

Grille Length :15-5/16"
Grille Width :7-3/8"
Cutout Length :14-3/8"
Cutout Width :6-7/16"
Total Depth :3-5/8"
Mounting Depth In-Wall :3-1/8"
Mid/Woofers :2@5-1/4"
Tweeter :1@1"
Product Weight :8 lbs
Frequency Response :28Hz - 30kHz
Sensitivity :89dB
Impedance :Nominal 4-8 Ohms
Recommended Amplifier Power :10 -250 WPC

DI6.5S	<p>Disappearing In-Wall Series 6-1/2" square in-wall loudspeaker High-Performance Speakers that Virtually Disappear in Your Room!</p> <p>Flangeless design & micro-perf grille minimize visibility Simple to install — no spackle work required Latest generation BDSS drivers for audiophile-grade sound quality Pivoting Pure Aluminum dome tweeters Axially Aligned design ensures broad, balanced coverage area GaussGrip™ magnetic grille fasteners Adjustable high-definition crossover Cast PolyStone™ baskets for rigidity without “ringing” Mounting Depth In-Wall :3-1/16" Woofers :6-1/2" Tweeter :1" (25 mm) Product Weight :4 lb. Frequency Response :26 Hz – 30 kHz Sensitivity :90 dB Impedance :Compatible with 4 – 8 Ohm outputs Min/Max Recommended Power :10/200 WPC</p>	<p>229.99/ea. 459.98/pr.</p>
DI5.5S	<p>Disappearing In-Wall Series 5-1/2" square in-wall loudspeaker SAME FEATURES AS DI6.5 WITH:</p> <p>Grille Length :7-3/8" Grille Width :7-3/8" Cutout Width :6-5/16" Cutout Length :6-5/16" Total Depth :3-5/8" Mounting Depth in-wall :3-1/16" Woofers :5-1/4" Tweeter :1" Product Weight :3.8 lb. Frequency Response :28 Hz – 30 kHz Sensitivity :89 dB Impedance :Compatible with 4 – 8 Ohm outputs. Min/Max Recommended Power :10/175 WPC</p>	<p>199.99/ea. 399.98/pr.</p>
DI8R	<p>Disappearing In-Wall Series 8" round in-wall loudspeaker SAME FEATURES AS DI6.5 WITH:</p> <p>Grille Length :8-5/16" , Grille Width :8-5/16" Cutout Length :7-1/4", Cutout Width :7-1/4" Total Depth :3-7/8" Outer flange (grille) diameter:9-3/4" Cut out diameter : 8-3/4" Depth from flange :3-7/8" Driver complement :1-inch pivoting Aluminum dome tweeter axially aligned with a 8" BDSS bass/midrange driver Frequency response :26Hz - 30kHz Impedance :4 - 8 Ohms Sensitivity :90 dB Recommended associated amplifier power :10 - 225 WPC Available finishes :Paintable white Weight :4.8 lb.</p>	<p>279.99/ea. 559.98/pr.</p>

DI6.5STR	<p>Disappearing In-Wall Series 6-1/5" stereo in-ceiling loudspeaker 229.99/ea. SAME FEATURES AS DI6.5 WITH: 459.98/pr.</p> <p>Stereo loudspeaker dual voice coil bass/midrange driver and dual tweeters is the perfect solution for hallways, kitchens, baths and commercial installations</p> <p>Outer flange (grille) diameter :8-5/16" Cut out diameter :7-1/4" Depth from flange :3-5/8" Driver complement :Two 3/4-inch pivoting Aluminum dome tweeters axially aligned with a 6-1/2" dual voice coil (stereo) BDSS bass/midrange driver Frequency response :26Hz - 30kHz Impedance :4 - 8 ohms Sensitivity :90 dB Recommended associated amplifier power :10 - 125 WPC Warranty :5 years Weight :4.4 lb.</p>
DI6.5R	<p>Disappearing In-Wall Series 6.5" round in-wall loudspeaker 199.99/ea. SAME FEATURES AS DI6.5 WITH: 399.98/pr.</p> <p>Outer flange (grille) diameter :8-5/16" Cut out diameter :7-1/4" Depth from flange :3-5/8" Driver complement :1-inch pivoting Aluminum dome tweeter axially aligned with a 6-1/2" BDSS bass/midrange driver Frequency response :26Hz - 30kHz Impedance :4 - 8 Ohms Sensitivity :90dB Recommended associated amplifier power :10 - 200 WPC Available finishes :Paintable white Warranty :5 years Weight :3.8 lb. each</p>
DI5.5R	<p>Disappearing In-Wall Series 5 1/4" round in-wall loudspeaker 159.99/ea. SAME FEATURES AS DI6.5 S WITH: 319.98/pr.</p> <p>Outer flange (grille) diameter :7-3/8" Cut out diameter :6-5/16" Depth from flange :3-5/8" Driver complement :1-inch pivoting Aluminum dome tweeter axially aligned with a 5-1/4" BDSS bass/midrange driver Frequency response :28Hz - 30kHz Impedance :4 - 8 Ohms Sensitivity :89 dB Recommended associated amplifier power :10 - 175 WPC Available finishes :Paintable white (see manual for painting instructions) Warranty :5 years Weight :3.7 lb</p>

POWERED SUBWOOFERS

Pro Sub 800	1 – 8” woofer 1 – 8” infrasonic radiator 300 watt amp Matte black or white H13 x W10-1/2 x D15-2/3	359.99
Pro Sub 60	1 – 8” woofer 150 watt amp Matte black H12-1/2 x W9-1/2 x D13-1/4	299.99
Supercube Trinity Signature	2 – 14” high pressure woofers 4 – 14” infrasonic radiators 2000 watt amp Gloss black H31-3/4 x W18 x D18	2,399.99
Supercube Reference	1 – 14” high pressure woofers 2 – 14” infrasonic radiators 1800 watt amp Gloss black H16-15/16 x W16-3/4 x D16-3/4	1,499.99
Supercube I	1 – 10” high pressure woofer 2 – 10” infrasonic radiator 1500 watt amp Gloss black H14-1/4 x W14-1/4 x D14-1/4	999.99
Supercube II	1 – 8” high pressure woofer 2 – 8” infrasonic radiators 1250 watt amp Gloss black H12-1/2 x W12 x D12	749.99
Supercube III	1 – 7-1/2” woofer 2 – 7-1/2” infrasonic radiators 650 watt Gloss black H10-1/4 x W10-1/4 x D10-1/4	599.99

Supercube 2000	1 – 7-1/2” woofer 2 – 7-1/2” infrasonic radiators 650 watt Gloss black 10-1/4 W x 10-7/8 D x 10-3/4	599.99
Pro Sub 1000	1 – 10” woofer 1 – 10” infrasonic radiator 300 watt amp Matte black H14-1/2 x W12 x D18	499.99
Pro Sub 800	1 – 8” woofer 1 – 8” infrasonic radiator 300 watt amp Matte black or white H13 x W10-1/2 x D15-2/3	359.99
Pro Sub 60	1 – 8” woofer 150 watt amp Matte black H12-1/2 x W9-1/2 x D13-1/4	299.99